


## 4/3 - 4/2 Directional valve elements with or without secondary relief valves, with or without LS connections

B8\_08... (EDBZ)

**RE 18300-52**

Edition: 09.2018

Replaces: 02.2016



Size 4

Series 00

Maximum operating pressure 310 bar (4500 psi)

Maximum flow 25 l/min (6.6 gpm)

Port connections G 3/8 SAE6 - M16x1.5

**NEW** spool position sensor available for this valve.  
See RE18300-30

### General specifications

Valve elements with 4 ways and 3, or 2, positions.

Control spools directly operated by solenoids with removable coils.

In the de-energized condition, the control spool is held in the central position by return springs.

Wet pin tubes for DC coils, with push rod for mechanical override; burnish surface treatment.

Coils can be rotated 360° around the tube.

Manual override (push-button or screw type) available as option.

### Contents

Ordering details	2
Symbols	2
Functional description	4
Technical data	4
Characteristic curves	6
External dimensions and fittings	7
Electric connection	8

## Ordering details

01	02	03	04	05	06	07	08	09	10
<b>B</b>	<b>8</b>		<b>08</b>					<b>0</b>	

<b>Family</b>		
01	Directional Valve elements EDB	<b>B</b>

<b>Type</b>		
02	Size 4	<b>8</b>

<b>Configuration</b>		
03	Standard	<b>0</b>
	With secondary valve on A	<b>1</b>
	With channels for Load Sensing	<b>4</b>

<b>Coil type</b>		
04	C36	<b>08</b>

<b>Spool variants<sup>1)</sup></b>		
05	4/3 operated on both sides a and b	<b>2</b>
	4/2 operated on side a only	<b>3</b>

<b>Voltage supply</b>		<b>31</b>	<b>07</b>	<b>04</b>	<b>03</b>	<b>01</b>	<b>00</b>	
06	Without coil	-	-	-	-	-	●	<b>00</b>
	12V DC	●	●	●	●	●	-	<b>0B</b>
	13V DC	-	-	-	-	●	-	<b>AD</b>
	24V DC	●	●	●	●	●	-	<b>0C</b>
	27V DC	-	-	-	-	●	-	<b>AC</b>
	48V DC	-	-	●	-	●	-	<b>0D</b>
	110V DC	-	-	-	-	●	-	<b>0E</b>
	24V AC (21.5 DC)	-	-	-	-	●	-	<b>0V</b>
	110V AC (98 DC)	-	-	-	-	●	-	<b>0W</b>
	230V AC (207 DC)	-	-	-	-	●	-	<b>0Z</b>

<b>Electric connections</b>		
07	Without coils	<b>00</b>
	With coils, without mating connector DIN EN 175301-803	<b>01</b> <sup>2)</sup>
	With coils, with bi-directional diode, without mating connector vertical Amp-Junior	<b>03</b>
	With coils, with bi-directional diode, without mating connector horizontal Amp-Junior	<b>04</b>
	With coils, with bi-directional diode, without mating connector DT04-2P	<b>07</b>
	With coils and bipolar sheathed lead 350mm (13,8 in) long	<b>31</b>




<b>Ports</b>		
08	G 3/8 DIN 3852	<b>3</b>
	M 16x1,5 DIN 3852	<b>U</b>
	9/16-18 UNF 2-B (SAE6)	<b>B</b>

<b>Secondary valves setting</b>		
09	50-210 bar (725-3045 psi)	<b>0</b> <sup>3)</sup>
	100-310 bar (1450-4500 psi)	<b>1</b>
	25-50 bar (362-725 psi)	<b>2</b>

<b>Options</b>		
10	No options	<b>No code</b>
	Standard	<b>0</b>
	Push-button type manual override	<b>P</b>
	Screw type manual override	<b>F</b>

● = Available    - = Not available

## Symbols



1) The required hydraulic symbol and spool variant can be chosen by consulting page 3.


2) For connectors ordering code see data sheet RE 18325-90.

3) Without secondary valve (versions B80\_; B84\_), the standard configuration corresponds to "0".




The secondary valves have a maximum flow capacity of 6 l/min (1.6 gpm).

Spool variants


08\_2 \_ \_



08\_3 \_ \_



## Functional description



The sandwich plate design directional valve elements B8\_08... are very compact direct operated solenoid valves which control the start, the stop and the direction of the oil flow. These elements basically consist of a stackable housing (1) with a control spool (2), one or two solenoids (5), and one or two return springs (4). When energized, the force of the solenoid (5) pushes the control spool (2) from its neutral-central position "0" to the required end position "a" or "b", and the required flow from P to A (with B to T),

or P to B (with A to T) is achieved. Once the solenoid is de-energized, the return spring (4) pushes the spool thrust washer (3) back against the housing and the spool returns in its neutral-central position.

Each coil is fastened to the solenoid tube by a ring nut (6). A pin (7) allows to push the spool (2) in emergency conditions, when the solenoid cannot be energized, like in case of voltage shortage.

## Technical data

General		
Valve element with 2 solenoids	kg (lbs)	1.34 (2.95)
Valve element with 1 solenoid	kg (lbs)	1.06 (2.34)
Ambient Temperature	°C (°F)	-20....+50 (-4....+122) (NBR seals)
MTTFd		150 years see RE 18350-51
Hydraulic		
Maximum pressure at P, A and B ports	bar (psi)	310 (4500)
Maximum pressure at T	bar (psi)	250 (3625)
Maximum inlet flow	l/min (gpm)	25 (6.6)
Maximum inlet flow with spool A201	l/min (gpm)	20 (5.3)
Hydraulic fluid		
General properties: it must have physical lubricating and chemical properties suitable for use in hydraulic systems such as, for example:		Mineral oil based hydraulic fluids HL (DIN 51524 part 1). Mineral oil based hydraulic fluids HLP (DIN 51524 part 2). For use of environmentally acceptable fluids (vegetable or polyglycol base) please consult us.
Fluid Temperature	°C (°F)	-20....+80 (-4....+176) (NBR seals)
Permissible degree of fluid contamination		ISO 4572: $\beta_{x \geq 75} X = 12 \dots 15$ ISO 4406: class 20/18/15 NAS 1638: class 9
Viscosity range	mm <sup>2</sup> /s	5....420


<b>Electrical</b>										
Voltage type	DC (AC only with RAC connection)									
Voltage tolerance (nominal voltage)	%	-10 .... +10								
Duty	Continuous, with ambient temperature ≤ 50°C (122°F)									
Coil wire temperature not to be exceeded	°C (°F)	150 (302)								
Insulation class	H									
Compliance with	Low Voltage Directive LVD 73/23/EC (2006/95/EC), 2004/108/EC									
Coil weight with connection EN 175301-803	kg (lbs)	0.215 (0.44)								
Voltage	V	12	13	24	27	48	110	24 +RAC (21,5)	110 +RAC (98)	230 +RAC (207)
Voltage type		DC	DC	DC	DC	DC	DC	DC	DC	DC
Power consumption	W	26	26	26	26	26	26	29	29	29
Current (nominal at 20 °C (68 °F))	A	2.15	2.0	1.10	1.0	0.54	0.27	1.20	0.29	0.14
Resistance (nominal at 20 °C (68 °F))	Ω	5.5	6.5	22	28	89	413	18	338	1430

**Note**

For applications with different specifications consult us

Code	Voltage [V]	Connector type	Coil description	Marking	Coil Mat no.
=OB 01	12 DC	EN 175301-803 (Ex. DIN 43650)	C3601 12DC	12 DC	R933000044
=OB 03	12 DC	AMP JUNIOR	C3603 12DC	12 DC	R933000047
=OB 04	12 DC	AMP JUNIOR Horizontal	C3604 12DC	12 DC	R933002913
=OB 07	12 DC	DEUTSCH DT 04-2P	C3607 12DC	12 DC	R933000048
=OB 31	12 DC	Cable 350 mm long	C3631 12DC	12 DC	R933000045
=AD 01	13 DC	EN 175301-803 (Ex. DIN 43650)	C3601 13DC	13 DC	R933000051
=AD 07	13 DC	DEUTSCH DT 04-2P	C3607 13DC	13 DC	R933000049
=OC 01	24 DC	EN 175301-803 (Ex. DIN 43650)	C3601 24DC	24 DC	R933000053
=OC 03	24 DC	AMP JUNIOR	C3603 24DC	24 DC	R933000057
=OC 04	24 DC	AMP JUNIOR Horizontal	C3604 24DC	24 DC	R933002914
=OC 07	24 DC	DEUTSCH DT 04-2P	C3607 24DC	24 DC	R933000058
=OC 31	24 DC	Cable 350 mm long	C3637 24DC	24 DC	R933000055
=AC 01	27 DC	EN 175301-803 (Ex. DIN 43650)	C3601 27DC	27 DC	R933000056
=AC 07	27 DC	DEUTSCH DT 04-2P	C3607 27DC	27 DC	R933000050
=OD 01	48 DC	EN 175301-803 (Ex. DIN 43650)	C3601 48DC	48 DC	R933000059
=OD 04	48 DC	AMP JUNIOR Horizontal	C3604 48DC	48 DC	R933002915
=OE 01	110 DC	EN 175301-803 (Ex. DIN 43650)	C3601 110DC	110 DC	R933000061
=OV 01	24 RAC	EN 175301-803 (Ex. DIN 43650)	C3601 21.5DC	21.5 DC	R933000054
=OW 01	110 RAC	EN 175301-803 (Ex. DIN 43650)	C3601 98DC	98 DC	R933000060
=OZ 01	230 RAC	EN 175301-803 (Ex. DIN 43650)	C3601 207DC	207 DC	R933000062


### Characteristic curves



Spool Variant	Curve no.				
	P>T	P>A	P>B	A>T	B>T
B201		3	3	2	2
E201		3	3	4	4
A201	2	1	1	1	1
C201	4	4	4	4	4
K201		3	3	4	3
X301		2	3	3	2
Y301		2	3	3	2

Measured with hydraulic fluid ISO-VG32 at 45° ±5 °C (113° ±9 °F); ambient temperature 20 °C (68 °F).

### Performance limits




Spool Variant	Curve no.
B201	1
E201	1
A201	4
C201	1
K201	3
X301	1
Y301	2


The performance curves are measured with flow going across and coming back, like P>A and B>T, with symmetrical flow areas.

In case of special circuit connections, the performance limits can change.

### Minimum flow for efficiency of LS control




### Lowest pressure setting curve for secondary valves



Secondary valve setting	Curve no.
50-210 bar (700-2950 psi)	0
100-310 bar (1400-4500 psi)	1
25-50 bar (350-700 psi)	2




**External dimensions and fittings**






- 1 Solenoid tube  $\varnothing$  14 mm (0.55 inch).
- 2 Ring nut for coil locking (OD 20.5 mm); torque 3-4Nm (2.2-3 ft-lb).
- 3 Identification label.
- 4 Clearance needed for connector removal.
- 5 Optional push-button manual override, EP type, for spool opening: it is pressure stuck to the ring nut for coil locking. Mat no. R933000042.
- 6 Optional screw type manual override, EF type, for spool opening:

- it is screwed (torque 6-7 (4.4-5.2 ft-lb)) to the tube as replacement of the coil ring nut. Mat no. R933006377.
- 7 Flange specifications for coupling to ED intermediate elements.
- 8 For tie rod and tightening torque information see data sheet RE 18301-90.
- 9 O-Rings for P and T ports.
- 10 Space needed for secondary valve.
- 11 A and B ports.

**Electric connection**

<p><b>00</b></p> 
<p><b>03</b> Protection class: IP 65 with female connector properly fitted (see drawing).</p> 
<p><b>31</b></p> 

<p><b>01</b></p> 
<p><b>04</b> Protection class: IP 65 with female connector properly fitted (see drawing).</p> 
<p><b>07</b> Protection class: IP 69 K with female connector properly fitted (see drawing).</p> 

**Bosch Rexroth Oil Control S.p.A.**  
Oleodinamica LC Division  
Via Artigianale Sedrio, 12  
42030 Vezzano sul Crostolo  
Reggio Emilia - Italy  
Tel. +39 0522 601 801  
Fax +39 0522 606 226 / 601 802  
compact-hydraulics-cdv@boschrexroth.com  
www.boschrexroth.com/compacthydraulics

© This document, as well as the data, specifications and other information set forth in it, are the exclusive property of Bosch Rexroth Oil Control S.p.a. It may not be reproduced or given to third parties without its consent. The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. It must be remembered that our products are subject to a natural process of wear and aging. Subject to change.